

# 868 / 656 High Performance Duo Mesh

A versatile, great value solution for low-mid level security needs



Image pictured with barbed wire top

High Performance Duo Mesh fencing is the original double wire mesh fencing system. It's hugely versatile, and great for perimeter fencing for applications such as schools, business perimeters (low-mid security) wildlife parks, and sports facilities.

The fencing system features twin horizontal wires either side of the vertical wire, and is available in 2 different options – 6mm verticals and twin 8mm horizontals or 5mm verticals and twin 6mm horizontals – traditionally known as 868 or 656). A wide range of heights, security ad ons and gates are available.



Scan for more info



## Features

Ideal for: Business perimeter, sports facilities, schools, wildlife parks

Anti-cut through, double wire panels

Wide range of height options.

Full range of RAL colours available



# 868 / 656 High Performance Duo Mesh

A versatile, great value solution for low-mid level security needs



## Technical product information

Standard	BS1722-14: 2017 BS EN ISO 1461:2009 BS EN 13438:2013
Panel type	Mesh and wire. Single vertical and double horizontal wires. Note: Duo Mesh Sports Rebound system panel type also available.
Panel width	2506mm
Wire diameter	6mm verticals and twin 8mm horizontals, or 5mm verticals and 6mm twin horizontals
Mesh size	200 x 50mm
Available heights	630mm to 6060mm. Fence heights above 3030mm are made of 2 or more panels.
Nominal heights	0.6 to 6.0 m
Finish	Polyester powder-coated to 60-80 microns or 160-200 microns with marine grade and metallics. Any RAL colour available.
Top Edge Projection	30mm
Panel installation	Bottom of panel approx. 40mm above ground
Security topping options	Cranked or straight extensions for barbed and razor wire depending on height of panel.
Post dimensions	60mm x 40mm to 120mm x 60mm depending on height of panel
Post centres	2520mm
Posts	RHS, galvanised after manufacture and polyester powder-coated to match fencing
Fixings	40m x 5mm full length clamp bar. M8 x 40mm stainless stell pin hex dome-head security screws. Sheardrive™ if required instead of pin hex.
Foundations	Set posts in holes minimum 300mm diameter x 800mm deep.
Warranty	Min. 15 years against manufacturing defects.

### Disclaimer:

Every care has been taken to ensure that all information provided on this data sheet is accurate. New Forest Fencing Ltd reserves the right to change the product specification at any time. Please ensure that you have the latest information which can be found on our website or by contacting our team.